



ASIALUBE CVTF NS 3 FULLY

Description

CVTF NS 3 (Continuously Variable Transmission Fluid) is a specialized transmission fluid developed for advanced automotive transmissions. This full-synthetic fluid offers superior lubrication, wear protection, and stability, ensuring smooth and efficient performance in continuously variable transmissions.

Application

CVTF NS 3 Continuously Variable Transmission Fluid ensures smooth and efficient performance in CVT systems. Specially formulated for optimal frictional properties, it enhances durability, minimizes wear, and maintains stability under various driving conditions, providing superior protection for the transmission.

Advantages

- IMPROVES OPERATION OF TRANSMISSION FRICTION CLUTCHES TO ENSURE SMOOTH SPEED-CONTROL
- REDUCES NOISE AND VIBRATION
- SUPERIOR PROTECTION AND LONG SERVICE LIFE
- GOOD RESISTANCE TO OXIDATION



Typical Characteristics

Name	Method	Units	ASIALUBE CVTF NS 3 FULLY
Density @ 15°C, Relative	ASTM D4052	g/ml	0.849
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	7.1
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s	34
Viscosity Index	ASTM D2270	None	179
Viscosity ,Brookfield@ -40°C (75W)	ASTM D2983	mPa.s (cP)	9200
Pour Point	ASTM D97	°C	-51
Flash Point, COC	ASTM D92	°C	214

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Product Performance Claims

- | | |
|--------------------------|----------------------|
| - TOYOTA CVTF TC,FE | -MINI COOPER EZL 799 |
| -HONDA HMMF,HCF 2 | -SUZUKI CVT GREEN |
| -NISSAN NS1,NS2,NS3, | 1,CVTF TC,NS 2 |
| -MITSUBISHI SP-III (CVT) | -PROTON CVT |
| -SUBARU ICVT | -PERODUA CVT |
| -FORD MERCON C | -VOLVO 4959 |

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.