



ASIALUBE DOT 3 BRAKE FLUID

Description

DOT 3 brake fluid is a glycol-based hydraulic fluid designed for use in automotive braking systems. Its high boiling point helps prevent vapor lock and ensures reliable brake performance. This fluid is compatible with rubber components and provides corrosion protection for brake system components.

Application

DOT 3 brake fluid is suitable for hydraulic brake systems in various vehicles, meeting or exceeding the industry standards. Used in cars, trucks, and motorcycles, it provides reliable brake performance by maintaining a high boiling point, preventing vapor formation, and protecting against corrosion, ensuring safe and effective braking.

Advantages

- EXCELLENT BRAKE PERFORMANCE
- CHEMICAL STABILITY
- BEST LUBRICATION EFFICIENCY



Typical Characteristics

Name	Method	Units	ASIALUBE DOT 3
Appearance	VISUAL	-	Red Liquid
pH	SAE J1703	pH	7-11
ERBP (Equilibrium Reflux Boiling Point)	SAE J1703	°C	Min 240
Density @ 20°C	IP 160	g/ml	1.05
Wet Equilibrium Reflux Boiling Point	SAE J1703	°C	min 145

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Product Performance Claims

- FMVSS 116 DOT 3 SAE J1703
- JISK 2233 MS119
- HI-TEMPERATURE 400°F

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.