



ASIALUBE DOT 4 BRAKE FLUID

Description

DOT 4 brake fluid is a glycol-based hydraulic fluid formulated for high-performance automotive braking systems. With a superior boiling point, it prevents vapor lock, ensuring efficient and consistent brake response. This fluid is compatible with anti-lock brake systems (ABS) and offers excellent corrosion protection for brake components.

Application

DOT 4 brake fluid is ideal for use in high-performance automotive braking systems, including those equipped with anti-lock brake systems (ABS). It provides superior thermal stability, preventing vapor lock and ensuring reliable brake performance. This fluid is suitable for various vehicles, offering corrosion protection and maintaining braking efficiency under demanding conditions.

Advantages

- EXCELLENT BRAKE PERFORMANCE
- CHEMICAL STABILITY
- BEST LUBRICATION EFFICIENCY



Typical Characteristics

Name	Method	Units	ASIALUBE DOT 4
Appearance	VISUAL	-	Clear And Bright Yellow Liquid
Density @ 20°C	IP 160	g/ml	1.07
ERBP (Equilibrium Reflux Boiling Point)	ASTM D1120	°C	260
Viscosity ,Kinematic -40°C	IP 71	mm ² /s	1200
Wet Equilibrium Reflux Boiling Point	SAE J1703	°C	165
pH	SAE J1703	pH	8.0
Water Content	ASTM D1123	%	0.15

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Product Performance Claims

- FMVSS 116 DOT 4 SAE J1703
- JISK 2233 MS119
- HI-TEMPERATURE 450°F

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.