

ASIALUBE ENGINE OIL 0W-20 FULLY

Description

0W-20 is a synthetic engine oil with a low viscosity, suitable for modern vehicles. It provides efficient lubrication, improves fuel economy, and ensures optimal engine performance in various temperatures. Ideal for meeting stringent automotive specifications, it supports engine longevity and reduces environmental impact.

Application

0W-20 is designed for modern engines, delivering optimal lubrication and fuel efficiency. Ideal for a range of temperatures, It meets stringent specifications for various vehicles, enhancing engine performance and longevity. Use as directed for intended applications, and reposibly dispose of used product to protect the environment.

Advantages

- LOW VISCOSITY, ADVANCED FULL SYNTHETIC FORMULA
- OUTSTANDING THERMAL AND OXIDATION STABILITY
- EXCELLENT LOW TEMPERATURE CAPABILITIES



Typical Characteristics

Name	Method	Units	ASIALUBE 0W-20 FULLY
Density @ 15°C, Relative	ASTM D4052	g/ml	0.856
Viscosity, Kinematic 100°C	ASTM D445	mm²/s	8.7
Pour Point	ASTM D97	°C	-42
Viscosity, CCS -35°C (0W)	ASTM D5293	mPa.s (cP)	5700
Viscosity, Kinematic 40°C	ASTM D445	mm²/s	49
Viscosity Index	ASTM D2270	None	161
Ash, Sulphated	ASTM D874	% wt	1.0
Flash Point, PMCC	ASTM D93	°C	220

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Product Performance Claims

- API SP/SN/SN PLUS/ SM/SL/SJ/ILSAC GF-6A
- ACEA A3/B4-12, ACEA C3-10
- MIL_L_4615D & CID A-A-52039B, FORD WSS-M2C947-A, CHRYSLER MS6395-H, MB 229.1, VW 505.00 FIAT 9.55535.D2
- MITSUBISHI, NISSAN, MAZDA, SUZUKI, TOYOTA, HONDA /ACURAHTO-6

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.