

## ASIALUBE ENGINE OIL 0W-30 FULLY

#### Description

0W-30 is a synthetic engine oil with a balanced viscosity, suitable for a variety of vehicles. Offering efficient lubrication and engine protection, it maintains stability in extreme temperatures. This oil ensures optimal performance, longevity, and fuel efficiency, meeting the demands of modern engines and environmental standards.

#### Application

0W-30 is formulated for diverse vehicles, providing superior lubrication and engine protection. Its balanced viscosity ensures stable performance in varying temperatures, promoting longevity and fuel efficiency. Comply with recommended usage guidelines ,and exercise environmentally responsible disposal practices for used product.

#### **Advantages**

- LOW VISCOSITY, ADVANCED FULL SYNTHETIC FORMULA
- OUTSTANDING THERMAL AND OXIDATION STABILITY
- EXCELLENT LOW TEMPERATURE CAPABILITIES



# Typical Characteristics

| Name                       | Method     | Units      | ASIALUBE 0W-30 FULLY |
|----------------------------|------------|------------|----------------------|
| Density @ 15°C, Relative   | ASTM D4052 | g/ml       | 0.842                |
| Viscosity, Kinematic 100°C | ASTM D445  | cSt        | 12.3                 |
| Viscosity, CCS -35°C (0W)  | ASTM D5293 | mPa.s (cP) | 5800                 |
| Viscosity, Kinematic 40°C  | ASTM D445  | cSt        | 72                   |
| Viscosity Index            | ASTM D2270 | None       | 169                  |
| Pour Point                 | ASTM D97   | °C         | -51                  |
| Flash Point, PMCC          | ASTM D93   | °C         | 200                  |
| Ash, Sulphated             | ASTM D874  | % wt       | 0.8                  |

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

### **Product Performance Claims**

- API SP/SN/SN PLUS/ SM/SL/SJ/ILSAC GF-6A
- ACEA A3/B4-12, ACEA C3-10
- MIL\_L\_4615D & CID A-A-52039B, FORD WSS-M2C947-A, CHRYSLER MS6395-H, MB 229.1, VW 505.00 FIAT 9.55535.D2
- MITSUBISHI, NISSAN, MAZDA, SUZUKI, TOYOTA, HONDA /ACURAHTO-6

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.