



ASIALUBE

ASIALUBE ENGINE OIL 10W-30 FULLY

Description

10W-30 is a versatile motor oil with a viscosity grade of 10 for cold starts and 30 for normal operating temperatures. It provides reliable lubrication and engine protection, suitable for a range of gasoline engines. This oil offers stability, cleanliness and optimal performance, ensuring smooth operation in various driving conditions.

Application

10W-30 full synthetic oil is ideal for gasoline engines, offering reliable lubrication and protection across a broad temperature range. Well-suited for various vehicles, it ensures optimal performance, engine cleanliness, and wear resistance. Perfect for everyday driving conditions, contributing to smooth operation and prolonged engine life.

Advantages

- SLUDGE BUILD-UP TO ENSURE LONG ENGINE LIFE
- MAINTAINING EXCELLENT VISCOSITY
- GOOD ENGINE CLEANLINESS



Typical Characteristics

Name	Method	Units	ASIALUBE 10W-30 FULLY
Viscosity @ 100°C	ASTM D445	cSt	11.31
Viscosity @ 210°F	ASTM D2161	SUS	63.9
Viscosity @ 40°C	ASTM D445	cSt	75.1
Viscosity Index	ASTM D2270		142
Low Temperature (°C) Cranking Viscosity	ASTM D5293	cP max	7,000 @ -25
Low Temperature (°C) Pumping Viscosity	ASTM D4684	cP max	50,000 @ -30
HT/HS Viscosity	ASTM D4683	cP min	2.9
Pour Point	ASTM D97	°F(°C) max	-33 (-36)
Flash Point, PMCC	ASTM D93	°C min	>200
Density @ 15°C, Relative	ASTM D4052		0.878
Pounds per Gallon			7.314

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Product Performance Claims

- API SP/SN/SN PLUS/ SM/SL/SJ/ILSAC GF-6A
- ACEA A3/B4-12, ACEA C3-10
- MIL_L 4615D & CID A-A-52039B, FORD WSS-M2C947-A, CHRYSLER MS6395-H, MB 229.1, VW 505.00
FIAT 9.55535.D2
- MITSUBISHI, NISSAN, MAZDA, SUZUKI, TOYOTA, HONDA /ACURAHTO-6

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.