



# ASIALUBE ASIALUBE ENGINE OIL 10W-30 MINERAL

## Description

10W-30 mineral oil offers superior engine protection with a viscosity grade of 10 for cold starts and 30 for regular operation. Formulated with high-quality additives, it enhances lubrication, reduces friction, and ensures optimal performance. Ideal for gasoline engines, providing advanced protection for a range of driving conditions.

## Application

10W-30 mineral oil is designed for gasoline engines, delivering advanced engine protection and performance. With a viscosity grade of 10 for cold starts and 30 for regular operation, it excels in diverse driving conditions. Ideal for modern Vehicles, ensuring reliable lubrication, reduced friction, and prolonged engine life.

## Advantages

- SLUDGE BUILD-UP TO ENSURE LONG ENGINE LIFE
- MAINTAINING EXCELLENT VISCOSITY
- GOOD ENGINE CLEANLINESS



## Typical Characteristics

Name	Method	Units	ASIALUBE 10W-30 MINERAL
Density @15C, Relative	ASTM D4052	g/ml	0.864
Viscosity, Kinematics 100°C	ASTM D445	mm <sup>2</sup> /s	10.5
Viscosity, Kinematics 40°C	ASTM D445	mm <sup>2</sup> /s	68
Viscosity Index	ASTM D2270	None	150
Viscosity, CCS -25°C (10W)	ASTM D5293	mPa.s (cP)	5000
Total Base Number, TBN	ASTM D2896	Mg KOH/g	9.8

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

## Product Performance Claims

- API SM/CI-4
- ACEA A3/B3-04, A3/B4-04
- MB 229.1
- VW 505.01/VW502.00-6

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.