



ASIALUBE

ASIALUBE ENGINE OIL 10W-30 SEMI

Description

10W-30 is a versatile motor oil with a viscosity grade of 10 for cold starts and 30 for normal operating temperatures. It provides reliable lubrication and engine protection, suitable for a range of gasoline engines. This oil offers stability, cleanliness and optimal performance, ensuring smooth operation in various driving conditions.

Application

10W-30 synthetic oil is ideal for gasoline engines, offering reliable lubrication and protection across a broad temperature range. Well-suited for various vehicles, it ensures optimal performance, engine cleanliness, and wear resistance. Perfect for everyday driving conditions, contributing to smooth operation and prolonged engine life.

Advantages

- SLUDGE BUILD-UP TO ENSURE LONG ENGINE LIFE
- MAINTAINING EXCELLENT VISCOSITY
- GOOD ENGINE CLEANLINESS



Typical Characteristics

Name	Method	Units	ASIALUBE 10W-30 SEMI
Appearance	VISUAL	-	Gold Brown
Viscosity , Kinematic 100°C	ASTM D445	mm ² /s	12.18
Viscosity , Kinematic 40°C	ASTM D445	mm ² /s	81.74
Viscosity Index	ASTM D2270	None	142
Ash,Sulphated	ASTM D874	% wt	0.97
Total Base Number, TBN	ASTM D2896	mg KOH/g	9.7
Pour Point	ASTM D97	°C	-39

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Product Performance Claims

- API SP/SN/SN PLUS/ SM/SL/SJ/ILSAC GF-6A
- ACEA A3/B4-12, ACEA C3-10
- MIL_L_4615D & CID A-A-52039B, FORD WSS-M2C947-A, CHRYSLER MS6395-H, MB 229.1, VW 505.00
FIAT 9.55535.D2
- MITSUBISHI, NISSAN, MAZDA, SUZUKI, TOYOTA, HONDA /ACURAHTO-6

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.