



ASIALUBE ASIALUBE ENGINE OIL 10W-40 MINERAL

Description

10W-40 mineral oil is a traditional engine lubricant with a viscosity grade of 10 for cold starts and 40 for regular operation. Composed of conventional base oils, it provides basic engine protection and lubrication. Suitable for older vehicles and moderate driving conditions, offering a cost-effective solution for routine maintenance.

Application

10W-40 mineral oil is ideal for older gasoline engines, offering basic yet effective lubrication and protection. With a viscosity grade of 10 for cold starts and 40 for regular operation, it suits moderate driving conditions. An economical choice for routine maintenance, ensuring engine performance and longevity in less demanding environments.

Advantages

- SLUDGE BUILD-UP TO ENSURE LONG ENGINE LIFE
- MAINTAINING EXCELLENT VISCOSITY
- GOOD ENGINE CLEANLINESS



Typical Characteristics

Name	Method	Units	ASIALUBE 10W-40 MINERAL
Density @15C, Relative	ASTM D4052	g/ml	0.869
Viscosity, Kinematics 100°C	ASTM D445	mm ² /s	14.2
Viscosity, CCS -25°C (10W)	ASTM D5293	mPa.s (cP)	6000
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s	96
Viscosity Index	ASTM D2270	None	151
Pour Point	ASTM D97	°C	-42
Flash Point, PMCC	ASTM D93	°C	205
Ash, Sulphated	ASTM D874	% wt	1.2

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Product Performance Claims

- API SM/CI-4
- ACEA A3/B3-04, A3/B4-04
- MB 229.1
- VW 505.01/VW502.00-6

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.