



ASIALUBE ASIALUBE ENGINE OIL 15W-40 MINERAL

Description

15W-40 mineral oil is a traditional engine lubricant with a viscosity grade of 15 for cold starts and 40 for regular operation. Composed of conventional base oils, it provides essential engine protection and lubrication. Ideal for older vehicles and heavy-duty applications, offering a cost-effective solution for routine maintenance.

Application

15W-40 mineral oil is well-suited for older gasoline and diesel engines, delivering fundamental lubrication and protection. With a viscosity grade of 15 for cold starts and 40 for regular operation, it's ideal for heavy-duty applications and older vehicles, ensuring reliable performance and longevity in demanding conditions.

Advantages

- SLUDGE BUILD-UP TO ENSURE LONG ENGINE LIFE
- MAINTAINING EXCELLENT VISCOSITY
- GOOD ENGINE CLEANLINESS



Typical Characteristics

Name	Method	Units	ASIALUBE 15W-40 MINERAL
Density @15C	ASTM D4052	g/ml	0.88
Viscosity, Kinematics 100°C	ASTM D445	mm ² /s	15.5
Viscosity, CCS -20°C (15W)	ASTM D5293	mPa.s (cP)	6500
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s	115
Viscosity Index	ASTM D2270	None	141
Ash, Sulphated	ASTM D874	% wt	1.0
Total Base Number, TBN	ASTM D2896	mg KOH/g	9.8
Pour Point	ASTM D97	°C	-42
Flash Point, PMCC	ASTM D93	°C	202

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Product Performance Claims

- API SM/CI-4
- ACEA A3/B3-04, A3/B4-04
- MB 229.1
- VW 505.01/VW502.00-6

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.