



# ASIALUBE ASIALUBE ENGINE OIL 20W-50 MINERAL

## Description

20W-50 mineral oil is a traditional engine lubricant with a viscosity grade of 20 for cold starts and 50 for regular operation. Comprised of conventional base oils, it provides essential engine protection and lubrication. Suitable for older vehicles and high-temperature environments, offering a cost-effective solution for routine maintenance.

## Application

20W-50 mineral oil is ideal for older diesel and gasoline engines in heavy-duty application. With a viscosity grade of 15 for cold starts and 40 for regular operation, it ensures essential lubrication and protection. Well-suited for trucks, construction equipment, and other demanding environments, promoting reliable engine performance and durability.

## Advantages

- SLUDGE BUILD-UP TO ENSURE LONG ENGINE LIFE
- MAINTAINING EXCELLENT VISCOSITY
- GOOD ENGINE CLEANLINESS



## Typical Characteristics

Name	Method	Units	ASIALUBE 20W-50 MINERAL
Density @ 15C, Relative	ASTM D4052	g/ml	0.8806
Viscosity, Kinematics 100°C	ASTM D445	mm <sup>2</sup> /s	18.0
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s	156.3
Viscosity Index	ASTM D2270	None	127
Pour Point	ASTM D97	°C	-33
Flash Point, PMCC	ASTM D93	°C	206

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

## Product Performance Claims

- API SM/CI-4
- ACEA A3/B3-04, A3/B4-04
- MB 229.1
- VW 505.01/VW502.00-6

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.