

ASIALUBE ENGINE OIL 5W-20 SEMI

Description

5W-20 is a multi-viscosity engine oil with a viscosity grade of 5 for winter and 20 for normal operating temperatures. It offers optimal flow and protection for engines, enhancing fuel efficiency and reducing wear. Ideal for a wide range of vehicles, providing year-round performance and engine durability.

Application

5W-20 is formulated for a wide range of vehicles,offering efficient lubrication and engine protection.With a balanced viscosity, it ensures smooth operation in diverse temperatures, enhancing fuel efficiency and meeting industry standars.Adhere to recommended usage guidelines, and responsibly dispose of used product to safeguard the environment.

Advantages

- LOW VISCOSITY, ADVANCED FULL SYNTHETIC FORMULA
- OUTSTANDING THERMAL AND OXIDATION STABILITY
- EXCELLENT LOW TEMPERATURE CAPABILITIES



Name	Method	Units	ASIALUBE 5W-20 SEMI
Density @ 15°C, Relative	ASTM D1298	g/ml	0.847
Viscosity, Kinematic 100°C	ASTM D445	mm²/s	8.2
Viscosity, CCS -30°C (5W)	ASTM D5293	mPa.s (cP)	3450
Viscosity, Kinematic 40°C	ASTM D445	mm²/s	44
Viscosity Index	ASTM D2270	None	160
Pour Point	ASTM D97	° C	-38
Flash Point, PMCC	ASTM D93	° C	210
Ash Sulphated	ASTM D874	% wt	0.8

Typical Characteristics

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Product Performance Claims

- API SP/SN/SN PLUS/ SM/SL/SJ/ILSAC GF-6A
- ACEA A3/B4-12, ACEA C3-10
- MIL_L_4615D & CID A-A-52039B, FORD WSS-M2C947-A, CHRYSLER MS6395-H, MB 229.1, VW 505.00 FIAT 9.55535.D2
- MITSUBISHI, NISSAN, MAZDA, SUZUKI, TOYOTA, HONDA /ACURAHTO-6

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.