

ASIALUBE ENGINE OIL 5W-30 FULLY

Description

5W-30 is a synthetic engine oil with a versatile viscosity, suitable for various vehicles. It provides efficient lubrication, ensuring smooth engine operation in different temperatures. This oil offers reliable protection, supports fuel efficiency, and meets industry standards for optimal engine performance and longevity.

Application

5W-30 is designed for diverse vehicles, delivering effective lubrication and engine protection. With a versatile viscosity, it ensures reliable performance in varying temperatures, promoting fuel efficiency and meeting industry standards. Follow Recommended usage guidelines, and responsibly dispose of used product to prioritize environmental well-being.

Advantages

- ENCHANCE ENGINE LONGEVITY VIA PROTECTION
- KEEPS ENGINE CLEAN BY PREVENTING BUIDUP
- LESS HYROCARBON POLLUTION



Typical Characteristics

Name	Method	Units	ASIALUBE 5W-30 FULLY
Density @ 15°C, Relative	ASTM D4052	g/ml	0.85
Viscosity, Kinematic 100°C	DIN 51562	mm²/s	11.6
Viscosity, CCS -30°C (5W)	DIN 51377	mPa.s (cP)	5950
Viscosity, Kinematic 40°C	DIN 51562	mm²/s	65
Viscosity Index	DIN ISO 2909	None	175
Pour Point	ASTM D5950	°C	-45
Flash Point, PMCC	ASTM D93	°C	196
Ash Sulphated	ASTM D874	% wt	0.8

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Product Performance Claims

- API SP/SN/SN PLUS/ SM/SL/SJ/ILSAC GF-6A
- ACEA A3/B4-12, ACEA C3-10
- MIL_L_4615D & CID A-A-52039B, FORD WSS-M2C947-A, CHRYSLER MS6395-H, MB 229.1, VW 505.00 FIAT 9.55535.D2
- MITSUBISHI, NISSAN, MAZDA, SUZUKI, TOYOTA, HONDA /ACURAHTO-6

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.