



ASIALUBE ASIALUBE ENGINE OIL SAE 40 MINERAL

Description

SAE 40 mineral oil is a high-viscosity lubricant designed for use in heavy-duty engines and industrial applications. Formulated from refined mineral base stocks, it provides excellent protection against wear, oxidation, and corrosion, ensuring optimal engine performance and longevity.

Application

SAE 40 mineral oil is commonly used as a lubricant in high-temperature, heavy-duty applications, such as industrial machinery and large engines. Its robust viscosity and thermal stability make it suitable for protecting critical engine components and ensuring smooth operation in demanding conditions.

Advantages

- SLUDGE BUILD-UP TO ENSURE LONG ENGINE LIFE
- MAINTAINING EXCELLENT VISCOSITY
- GOOD ENGINE CLEANLINESS



Typical Characteristics

Name	Method	Units	ASIALUBE SAE 40 MINERAL
Density @15C,Relative	ASTM D4052	g/ml	0.956
Appearance	VISUAL	-	Clear and Bright
Viscosity,Kinematics 100°C	ASTM D445	mm ² /s	14.7
Viscosity,Kinematic 40°C	ASTM D445	mm ² /s	142
Viscosity Index	ASTM D2270	None	101
Flash Point, PMCC	ASTM D93	°C	170

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Product Performance Claims

- API EXCEEDS SF/CF
- DETROIT 7SE-270
- MIL-L-2104F,CATERPILLAR TO-2,MACK EO-K/2

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.