



ASIALUBE

ASIALUBE POWER STEERING FLUID PSF-S

Description

POWER STEERING FLUID PSF-S is a specialized hydraulic fluid designed for power steering systems. Formulated with high-quality base oils and additives, it ensures smooth operation by providing excellent wear protection, oxidation stability, and compatibility with seals. Ideal for enhancing steering performance and prolonging the life of power steering components.

Application

POWER STEERING FLUID PSF-S is recommended for use in power steering systems of various vehicles, including cars, trucks, and SUVs. Its advanced formula ensures smooth and responsive steering performance, protects against wear, and maintains seal compatibility, contributing to the longevity and efficiency of power steering components.

Advantage

- SMOOTHLS POWER STEERING OPERATION
- PROTECTS SEALS AND HOSES
- RESISTS FOAMING TENDENCY
- PREVENT LEAKS , SQUEALS ,RUST AND CORROSION



Typical Characteristics

Name	Method	Units	ASIALUBE PSF-S
Density @ 15°C, Relative	ASTM D1298	g/ml	0.883
Colour	ASTM D1500	-	Red
Appearance	VISUAL	-	Clear & Bright
Viscosity ,Kinematic 100°C	ASTM D445	mm ² /s	7.1
Viscosity, Brookfield @ -40°C	ASTM D2983	mPa.s (cP)	45000
Viscosity ,Kinematic 40°C	ASTM D445	mm ² /s	36
Viscosity Index	ASTM D 2270	None	162
Flash Point, PMCC	ASTM D93	°C	180

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Product Performance Claims

SUITABLE TO USE OR EQUIVALENT TO:

- DAIMLERCHRYSLER MS 5931
- FORD ESW-M2C12B-C& D
- GM 9985010
- HONDA PSF

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.